

ZCA (XSZC) vacuum solenoid valve



ZCA-15



ZCA-20



ZCA-25



ZCA-32



ZCA-40



ZCA-50

Product features

- Suitable medium: gas
- Medium temp.: -5°C-80°C
- Action type: direct acting type or diaphragm type
- Working pressure: -1 ~1bar
- Valve body material: brass(forged),stainless steel(precision casting)
- Diaphragm sealing: material: NBR
- Coil Protection level: Plastic coil IP65

Structure features

- Low voltage or vacuum pipeline
- Big flow
- Directing acting or diaphragm type with fast reaction
- Coil power consumption is high

Technology data

Model	Connecting Method	Diameter	Cv value	Length (mm)	Height (mm)	Medium temp.	Working pressure (pressure differential)	Rated voltage
ZCA025-08	G1/4"	2.5	0.23	40	75	-5~80°C	-1~1 bar	220VAC/50HZ 110VAC/50HZ 26VA-30VA DC24 DC12 18W ~ 30W Tolerance: ± 10% Other voltage can becustomized
ZCA040-10	G3/8"	4	0.6	47	85			
ZCA160-10	G3/8"	16	4.8	64	105			
ZCA-15	G1/2"	16	4.8	64	105			
ZCA-20	G3/4"	20	7.6	65	110			
ZCA-25	G1"	25	12	85	125			
ZCA-32	G1 1/4"	32	24	95/110	135/160			
ZCA-40	G1 1/2"	40	28	110/112	160/165			
ZCA-50	G2"	50	45	118/155	175/190			

Internal structure & profile size figure

