

### Anti-Corrosion Glass Rotameter

MODEL	DN	Range		Parameter	Size
		Liquid	Gas		
LZB-15F	φ15 (mm)	16-160 l/h	0.25-2.5 Nm <sup>3</sup> /h	Precision: ± 4 % Pressure ≤0.6Mpa Temp.: 0-60 °C	Length : 470±2.5 mm
		25-250 l/h	0.4-4 Nm <sup>3</sup> /h		
		40-400 l/h	0.6-6 Nm <sup>3</sup> /h		
LZB-25F	φ25 (mm)	40-400 l/h	1-10 Nm <sup>3</sup> /h	Precision: ± 2.5% Pressure ≤0.6Mpa Temp.: 0-60 °C	Length : 470±2.5 mm
		60-600 l/h	1.6-16 Nm <sup>3</sup> /h		
		100-1000 l/h	2.5-25 Nm <sup>3</sup> /h		
LZB-40F	φ40 (mm)	160-1600 l/h	4-40 Nm <sup>3</sup> /h	Precision: ± 2.5% Pressure ≤0.6Mpa Temp.: 0-60 °C	Length : 470±2.5 mm
		250-2500 l/h	6-60 Nm <sup>3</sup> /h		
LZB-50F	φ50 (mm)	400-4000 l/h	10-100 Nm <sup>3</sup> /h	Precision: ± 2.5% Pressure ≤0.6Mpa Temp.: 0-60 °C	Length : 470±2.5 mm
		600-6000 l/h	16-160 Nm <sup>3</sup> /h		
LZB-80F	φ80 (mm)	1-10 m <sup>3</sup> /h	50-250 m <sup>3</sup> /h	Precision: ± 2.5% Pressure ≤0.4Mpa Temp.: 0-60 °C	Length : 470±2.5 mm
		1.6-16 m <sup>3</sup> /h	80-400 m <sup>3</sup> /h		
LZB-100F	φ100 (mm)	5-25 m <sup>3</sup> /h	120-600 m <sup>3</sup> /h	Precision: ± 2.5% Pressure ≤0.4Mpa Temp.: 0-60 °C	Length : 470±2.5 mm
		8-40 m <sup>3</sup> /h	200-1000 m <sup>3</sup> /h		

گروه صنعتی متالیکان فارس

Metalicanfars.com