

Long tube (No Guide Rod)				Short Tube (With Guide Rod)			
Model	DN & Connect	Length (mm)	Flow Range	Model	DN & Connect	Length (mm)	Flow Range
LZS-15	DN15 Female BSP 1/2"	280	10-100L/h	LZS-15	DN15 Female BSP 1/2"	280	10-100L/h
			16-160L/h				16-160L/h
			25-250L/h				25-250L/h
			40-400L/h				40-400L/h
			60-600L/h				60-600L/h
			80-800L/h				80-800L/h
			100-1000L/h				100-1000L/h
				LZS-20	DN20 Female BSP 1/2"	231	60-600L/h
							100-1000L/h
							160-1600L/h
LZS-25	DN25 Female BSP 3/4"	380	100-1000L/h	LZS-25	DN25 Female BSP 3/4"	226	100-1000L/h
			160-1600L/h				
			250-2500L/h				
			300-3000L/h				
LZS-32	DN32 Female BSP1"	288	0.4 - 4 m³/h	LZS-32	DN32 Female BSP1"	288	400-4000L/h
			0.6 - 6 m³/h				600-6000L/h
LZS-40	DN40 Female BSP 1-1/4"	430	0.4 - 4 m³/h				
			0.6 - 6 m³/h				
			1 - 10 m³/h				
			1.2 - 12 m³/h				
LZS-50	DN50 Female BSP1.5"	430	0.4 - 4 m³/h	LZS-50	DN50 Female BSP1.5"	341	1 - 10 m³/h
			0.6 - 6 m³/h				1.6 - 16 m³/h
			1 - 10 m³/h				
			1.6 - 16 m³/h (with guide rod)				
				LZS-65	DN65 Female BSP2"	430	2.5 - 16 m³/h
			5 - 25 m³/h				
			8 - 40 m³/h				
			12 - 60 m³/h				
Flange connection							
LZS-65F	DN65 Female BSP2"	430	2.5 - 16 m³/h	LZS-80F	Flange	540	2.5 - 16 m³/h
			5 - 25 m³/h				5 - 25 m³/h
			8 - 40 m³/h				8 - 40 m³/h
			12 - 60 m³/h				12 - 60 m³/h
LZS-100F	DN100 Flange	550	12 - 60 m³/h	LZS-125F	DN125 Flange	550	14 - 90 m³/h
							14 - 90 m³/h
							14 - 90 m³/h
LZS-150F	DN 150 Flange	560	Customized				

گروه صنعتی متالیکان فارس
Metalicanfars.com